

TP-701CCQ

fully automatic strapper

2010.03.18





Product Range

TP-701CCQ Corrugated Strapper




TP-701CCQ

Corrugated Strapper with Bundle Squarer



TP-701CC
Corrugated Strapper






TP-701CCQ Corrugated Strapper

Compact Strapping Head

30% fewer parts than other brands



- Fewer adjustments
- Fewer wear components
- Less maintenance






Hinged Top Plates



TP-701CCQ Corrugated Strapper

Easy maintenance

- Quick cleaning
- Quick inspection
- Easy maintenance






Adjustable Table Height



TP-701CCQ Corrugated Strapper

Meet various height requirements

Adjustable to any height between 750 mm and 1100 mm.





TP-701CCQ Corrugated Strapper

Convenient

Waist-High Auto Strap Feeding User Friendly



Without the need to access the bottom of the machine.





Siemens PLC Control

& HMI (Touch Panel)

TP-701CCQ Corrugated Strapper





Provide easy adjustments, operating instruction and troubleshooting guides.

SQUARE	OFF	
PRESS HAR	ON	1
STOPPER	ON	
STRAPHUNDLE	CI.	
MODE	AUTO	
START	DESCRIPTION OF THE PARTY OF THE	





Bundle Stop and Side Squarer

(TP-701CCQ ONLY)



Ensure the bundle integrity

Quick bundle squaring for strapping process





- Automatic strap loop ejection
- Patented jammed strap ejection device
- Full-width pneumatic press
- Single, double, continuous strapping or transit mode
- Knurled Roller-driven table top
- Strap end detection and ejection
- Variable conveyor speed





- Light tree alarm (dual lamp)
 - Figure 1 Enable user to notice the abnormal phenomenon of machine
- Operator friendly low strap sensor (triple lamp)
 - Alarm user to prepare one new coil of strap for replacement
- Safety Guards
 - Provide maximum operator safety





Available Arch Size

TP-701CCQ Corrugated Strapper

Model	Arch Size (mm)	Strapping Speed (bundle/min.)
TP-701CC-L	1650 x 500	Single strap: 26 Parallel straps: 15
TP-701CCQ-L		Single strap: 24 Parallel straps: 15
TP-701CC-M	1250 x 500	Single strap: 28 Parallel straps: 16
TP-701CCQ-M		Single strap: 24 Parallel straps: 16
TP-701CC-S	850 x 500	Single strap: 30 Parallel straps: 17
TP-701CCQ-S		Single strap: 24 Parallel straps: 17

Dimension drawings are on request.





- Strap width: 5 mm, 6 mm, and 9 mm
- Strap Tension: 8-35 kg
- Pneumatics: 6 bars; 7.5 liters/cycle free air
- Package size: minimum 300mm(L) x 200mm(W)
- Power: 110V, 220V, 230V, 380V, 400V 50/60Hz 1PH or 3PH






Combine with C-BT Bundle Turner

TP-701CCQ Corrugated Strapper

Save strap



90° bundle turning for strapping to the carton flute





The World's Value Leader!!

Always more than you expect.

Never try, never know!!

