

Corrugated Inline Squaring and Strapping System

TP-CIL TransCorrLiner

TRANSPAK TP-CIL TransCorrLiner is a high-speed corrugated inline squaring and strapping system. It can meet the speed requirement of the fastest Flexo Folder Gluer and Casemaker.











TP-CIL TransCorrLiner

Main Features

Compact & Robust Strapping Head TP-CIL-SH

TP-CIL uses the latest DC brushless technology in sealing head, needle, and non-center strapping to provide the highest level of reliability and durability. Thermocouple controlled heat sealing system assures consistent and high sealing efficiency.



➤ Intelligent Pusher Optimizes Speed (patents pending)

Intelligent self-positioned pusher detects bundle length automatically. It streamlines production line and increases strapping speed.



➤ Automatic Bundle Size Setup System
The automatic setting modes makes TP-CIL
fast set up for bundle size shange in 15

fast set-up for bundle size change in 15 seconds. It minimizes the costly downtime.

> Strapping in the Flute Direction

Strapping in the transport direction, in line with the flutes.



Good for Inexpensive Narrow Strap with Maximum Efficiency

The drape-strap feeding design allows TP-CIL use economical PP strap. Cost saving.

All specifications are subject to change without notice.

More Features

- Siemens PLC and HMI (touch panel) Provide easy adjustments, TEACH-IN programming, and troubleshooting guides.
- Non-center Strapping Strapping position is adjustable for different requirements.
- Hot Standby Mode (Two heads version only)

While performing single strapping, the 2nd strapping head is always standby for saving downtime.


Options

- > Powered alignment device
- > Air conditioner for control box
- > Belt driven conveyor for the last bundle
- > Energy saving transit with auto sleep mode
- > Uplifted support
- > Upstream accumulating conveyor
- ➤ Auto splicer (to be available during 1st half of 2017)

Stack Sizes

Machine model	Width A (mm)		Length B (mm)		Height C (mm)	
	min	max	min	max	min	max
TP-CIL-13S	180	1300	180	1300	50	350
TP-CIL-13T	450	1300	180	1300	50	350
TP-CIL-16S	180	1600	180	1600	50	350
TP-CIL-16T	450	1600	180	1600	50	350

* S(single) : one strapping head T(twin) : two strapping heads





SPAK 15F-1, NO. 17, SEC. 1, CHENGDE ROAD, TAIPEI 103, TAIWAN

TRANSPAK EQUIPMENT CORP. TEL: 886 2 2555 2515 FAX: 886 2 2555 2516